





<b>REF.</b>	<b>FA 40 500 XX</b>
<b>CE</b>	EN 354:2010
<b>LG.</b>	1.0 m   1.5 m   1.8 m
<b>MAT.</b>	 PA 11 mm Polyamide
	---
<b>R (kN)</b>	22 kN
<b>kg</b>	0.17 KG   0.20 KG   0.22 KG

<b>MAT.</b>		<b>R (kN)</b>
<b>Matière</b>	<b>Matière connecteurs</b>	<b>Résistance (en kN)</b>
<b>Material</b>	<b>Material of connectors</b>	<b>Resistance (kN)</b>
<b>Material</b>	<b>Material de los conectores</b>	<b>Resistencia (en kN)</b>
<b>Materia</b>	<b>Materie connettori</b>	<b>Resistenza (in kN)</b>
<b>Material</b>	<b>Material der Verbinder</b>	<b>Belastbarkeit (in kN)</b>



<b>HS CODE</b>
56090000
<b>CARTON SIZE / PCS.</b>
60 X 40 X 24 cm / 50
<b>AET (UE) N°2777/10360-02/E05-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland