






<b>REF.</b>	<b>FA 40 502 XX</b>
<b>CE</b>	EN 354:2010
<b>LG.</b>	1.0 m   1.5 m   1.8 m
<b>MAT.</b>	 PA 11 mm Polyamide
	--- /  <b>STEEL</b>
<b>R (kN)</b>	22 kN
	0.66 KG   0.68 KG   0.72 KG

<b>MAT.</b>		<b>R (kN)</b>
<b>Matière</b>	<b>Matière connecteurs</b>	<b>Résistance (en kN)</b>
Material	Material of connectors	Resistance (kN)
<b>Material</b>	<b>Material de los conectores</b>	<b>Resistencia (en kN)</b>
Materia	Materie conettori	Resistenza (in kN)
<b>Material</b>	<b>Material der Verbinder</b>	<b>Belastbarkeit (in kN)</b>

<b>HS CODE</b>
56090000
<b>CARTON SIZE / PCS.</b>
FA 40 502 10, FA 40 502 15 : 40 x 40 x 24 cm / 25 FA 40 502 20 : 60 x 40 x 24 cm / 25
<b>AET (UE) N°2777/10360-02/E05-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland